EEPROM Information

USB Descriptor Table

Vendor ID: [   ]   Product ID: [   ]

Vendor Desc: [   ]

Product Desc: [   ]

PCB Revision: [   ]

Serial Number: [   ] [   ]

Attributes: I/O test:Off
               Read/Write test:Off

External Firmware Information

☐ Filename: [   ]

Checksum: [   ] **1**

[Config] [**EEP ROM Edit**]

[Load]   [Cancel]

EEPROM Editor - Prolific

USB Descriptor Table

Vendor ID: [067B]   Product ID: [   ]

Vendor Desc: [Prolific Technology Inc.]

Product Desc: [USB-SATA Bridge]

PCB Revision: [0100]

Serial Number: [PROLIFICMP] [000000001] ☑ Exceed 10-Bytes

Attributes: ☑ Self-Powered

External Firmware and AutoRun ISO Filename

3 ☐ Filename: [   ] [...] **4**

Checksum: [   ]

☐ ISO Filename: [   ] [...]

Firmware Information

▼ No device

Version: [   ]

2 [Read chip]

5 [Write configure & FW]

[Load EEP]

[Save to EEP]

[Erase Chip]

[More >>]

7 [Exit]

Prolific Engineer configuration

FW checksum : B71B
ound device to config
asing chip...   OK
ogramming & Verify chip   OK
erify FW...   OK
erify configure...   **6**   OK

Config device pass

ⓘ Config device completely

[OK]

Instructions:

Connect device and make sure the system can see the enclosure
Install flash program
Run the installed MultiPortConfigureEEP Program tool
1 Click EEP ROM Edit
2 Click Read chip
3 Check and 4 Select firmware file
5 Click Write configure & FW
6 Review and make sure device pass, click OK
7 Exit